



€ 31.032 VAT excluded

L 35 ADAPTOR S		L35 F	L 35 H
Wheelbase	X	2760	3360
Overall length	K	5295	6015
Body length min. ⁽¹⁾	W	3545	4265
Body length Max. ⁽¹⁾	W	3830	4500
Rear overhang	Y	1435	1555
Chassis height	T		715
Overall height	H	2150	2160
Rear axle width	L		1860
Cab width ⁽²⁾	L1		1815
Body width ⁽³⁾	C		2120
Front axle to back of cab	D min		650
Front overhang	A		1100
Frame internal size	I		700
Front track	C1		1400
Rear track	C2		1425
Minimum Road Clearance	-		180
Turning diameter (m) ⁽⁴⁾	-	10,0	11,9
WEIGHT (kg)			
Unladen weight ⁽⁵⁾		2200	2250
Unladen weight front axle		1530/670	1550/700
Minimum weight vehicle equipped			2585
Gross Vehicle Weight (GVW)			3500
Front/rear total weight			2100 / 2435
Max trailer weight unbraked/Max trailer weight braked			750 / 3500

1. The length of the body refers to a uniformly loaded vehicle, up to the maximum capacity on each axle (dimensions declared in C.O.C. with no chassis modifications).
2. Excluding turn signal and side mirrors
3. Possible widths with optional mirror brackets 1860/1945 – 1945/2120 – 2120/2275
4. Curb to curb turning diameter
5. The Unladen weight include spare wheel, full fuel tank and driver, optional excluded. NEES + 35 Kg (25/10)

L 35 ADAPTOR S - Wheelbase (mm) F 2760 - H 3360

FEBRUARY 2021

€ 31.032 (**)

Equipment	NEES 2 (only Wheelbase H)	€ 1290 (**)
-----------	---------------------------	-------------

(**)VAT excluded

Standard features

- | | | |
|---|--|--|
| <ul style="list-style-type: none"> • EGR - DPD - SCR • MID display • Engine exhaust brake • Suspended seat • Immobilizer | <ul style="list-style-type: none"> • Reverse warning buzzer • Central locking with remote control • Power operated windows • Day-time running lights | <ul style="list-style-type: none"> • Radio DAB+ with USB • Fog lamps Fr and Rr • Head lamps control levelling • Steering adjustable (tilting and height) |
|---|--|--|

Optional

- | | |
|---------------------------|-------------|
| • Air conditioning | € 1089 (**) |
| • Body builder Controller | € 354 (**) |

Engine

ISUZU 4JJ1E6N Diesel Engine 4 cylinders
 Intercooler, common-rail with direct injection
 Variable-geometry turbocharger
 DISPLACEMENT 2999 cm³
 POWER 110kW (150 hp) 2800 rpm.
 TORQUE. 375 Nm 1600 – 2800 rpm
 EMISSIONS REGULATIONS EURO VI OBD-D.

Safety systems

ABS with BAS (Brake Assist System)
ESC (Electronic Stability Control) with ASR
 SRS Driver Airbag

Tank

68 L Wheelbase F – 93 L Wheelbase H	16 L Ad-Blue®
--	---------------

Gearbox and Final drive ratio

5 gear MYY5A – 5.315 - 2.908 - 1.558 - 1.000 - 0.721;
 Reverse 5.068;
 Final gear ratio 3.909 (43/11)

Transmission control

Manual	NEES 2
---------------	--------

Dimensions of the chassis

Width 50 mm, Height 180 mm, Thickness 4 mm

Number of seats

3

Axle

2
 the rear one with twin wheels.

Tires

Front 205/75 R16C simple.
 Rear 205/75 R16C dual.

Brakes

Front and rear: ventilated discs with asbestos-free linings. Hydraulic system, with vacuum brake booster EEC standards with ABS, independent circuits on both axles. Drum parking brake on the transmission shaft.

Suspensions

Front: Independent suspension with coil spring and double wishbone. Rear: Multi semi elliptical alloy steel leaf spring. Hydraulic double acting shock absorbers.

Electric system

Nominal voltage 24V - Generator 90A - 2 x Battery 70Ah